

## VARIABLE SYSTEM COMPONENTS



<b>Model</b>	ECO-NTSS150	HWS-FLT	EST-CP150	EST-CP250	EST-CP400	EST-CP500
<b>Part Number</b>	9320-2337	9320-2170	9320-2548	9320-2149	9320-2519	9320-2150
<b>Resin Vessel (qty) Size</b>	(2) 8" x 8"	(2) 8" x 8"	(2) 10" x 54"	(2) 11" x 54"	(2) 16" x 65"	(4) 13" x 64"
<b>Empty Bed Volume (per tank)</b>	0.40 ft <sup>3</sup>	0.40 ft <sup>3</sup>	2.29 ft <sup>3</sup>	3.68 ft <sup>3</sup>	6.95 ft <sup>3</sup>	3.68 ft <sup>3</sup>
<b>Resin Volume (per tank)</b>	0.40 ft <sup>3</sup>	0.40 ft <sup>3</sup>	1.50 ft <sup>3</sup>	2.50 ft <sup>3</sup>	4.00 ft <sup>3</sup>	2.50 ft <sup>3</sup>
<b>Bed Depth</b>	17"	17"	39"	40"	47"	40"
<b>Free Board</b>	NA	NA	15"	14"	18"	14"
<b>Salt Capacity</b>	70 lbs	200 lbs	500 lbs	500 lbs	500 lbs	500 lbs
<b>INLET WATER QUALITY</b>						
<b>Pressure Range (Dynamic Pressure)</b>	25 - 125 psi	25 - 125 psi	25 - 125 psi	25 - 125 psi	25 - 125 psi	25 - 125 psi
<b>Temperature Range</b>	35 - 150°F	35 - 150°F	35 - 100°F	35 - 110°F	35 - 100°F	35 - 110°F